



**KODAK**

Universal Backlit Film / 8 mil

## Universal compatibility at a competitive price

### Economical film with excellent image quality

This heavyweight front-print backlit provides excellent pigment and dye image quality, high-speed drying and universal compatibility at a competitive price.

### Quick-dry time

With a heavyweight durable polyester Duratrans®-like support, this film offers excellent print handling and finishing characteristics, exceptional color saturation and a quick dry time.

### FEATURES:

- Resists flaking when cut
- Added scratch resistance
- Water-resistant for outdoor use

### APPLICATIONS:

- Backlit airport signage
- Backlit mall and shopping center signage

US Size	Euro Size	Quantity	SKU
24" x 100'	61,0 cm x 30,5 m	1 Roll	223712-00
36" x 100'	91,4 cm x 30,5 m	1 Roll	223773-00
42" x 100'	106,7 cm x 30,5 m	1 Roll	223774-00
50" x 100'	111,8 cm x 30,5 m	1 Roll	223775-00
60" x 100'	152,4 cm x 30,5 m	1 Roll	223776-00





## Universal Backlit Film / 8 mil

Properties	Specifications
<b>Material</b>	Polyester
<b>Gauge</b>	8 mil / 275g
<b>Gloss Level</b>	<5
<b>Opacity</b>	>70
<b>Whiteness</b>	>157
<b>Tear Strength</b>	NA
<b>Printer/Ink Compatibility</b>	Compatible with all thermal and piezo inkjet printers using water-based dye and pigment-based inks.
<b>Software Settings</b>	The heavyweight coated or matte setting in most RIPs is appropriate; however, we recommend a custom ICC profile for optimal results. Please refer to <a href="http://www.brandmanagementgroup.com">www.brandmanagementgroup.com</a> for ICC profiles for some printers.
<b>Lightfastness</b>	The fading time of inkjet ink is a direct result of the inks that you choose to use and the environment where the print is displayed. Contact the ink manufacturer for light-fastness data.
<b>Finishing/Post Processing</b>	It is always recommended that a protective laminate be applied after printing. Hand applying laminate is not recommended. Pressure-sensitive or thermal laminates can be used. Before applying the laminate, allow the image to dry for 24 hours.
<b>Optimal Service Environment</b>	72° F (21° C), 50% R.H. For end use: 0-300° F.
<b>Flame Spread Classification</b>	Class A Fire Rating
<b>Handling Recommendations</b>	Due to the absorptive nature of the coating, you should avoid touching the coated surface. It's always recommended that cotton gloves be used when handling inkjet coated materials.
<b>Ideal Storage Conditions</b>	70°F (21°C), 50% R.H. (a controlled environment is recommended); store in original packaging.
<b>Shelf Life</b>	1 year from the BMG ship date when stored in proper conditions.



**Product Performance & Suitability:** All of the descriptive information and recommendations for the use of Kodak products should be used only as a guide. Furnishing such information and recommendations shall in no event constitute a warranty of any kind by BMG. All Purchasers of Kodak products shall independently determine the suitability of the material for the purpose for which it is purchased. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither the seller nor the manufacturer shall be liable either in the tort or contract for any loss or damage, direct, incidental or consequential (including loss of profits or revenue) arising out of the use of or the inability to use the product. No statement or recommendation not contained herein shall have any force or effect in agreement signed by officers of seller and manufacturer.

Eastman Kodak Company 343 State Street Rochester, NY 14650 USA +1-866-563-2533 in North America. Produced using Kodak Technology.  
©Kodak, 2017. Kodak, Flexcel, Squarespot, Staccato and the Kodak Logo are trademarks of Kodak.  
Subject to technical change without notice. U.FLX.865.0916.en.13

[KODAKWFMedia.com](http://KODAKWFMedia.com)

